

Eagle O.S.&D.®

Eagle O.S. & D.® Hose



Application: For oil/water suction and delivery service.

Tube: Oil and fuel resistant conductive nitrile (NBR)

Reinforcement: Multiple high tensile synthetic tire cords (polyester cords) with steel wire helix

Cover: Oil, weather and ozone resistant, cloth impression, black synthetic rubber

Temperature: -40°F to +194°F

Lengths: 10' and 20' standard lengths

Packaging: Custom skids

Branding: EAGLE OIL SERVICE S&D® CARGO 250 MAX WP #Q## MEETS USCG 33CFR 154.500

Couplings: Built-in pipe flanges fixed x floating (ANSI B16.5).

Safety Factor: 4:1

Features:

- All Eagle OS&D® Hose assemblies are hydro-tested and certified at the factory.
- Tested following U.S.C.G. certification standards.

Part #		ID	OD	WP	Bend Radius	Weight*	
10'	20'	in	in	psi	in	lbs	
						10'	20'
009-0643-0010	009-0643-0020	4	5-1/2	250	19	100	176
009-0963-0010	009-0963-0020	6	7-1/2	250	29	183	265
009-1283-0010	009-1283-0020	8	9-1/2	250	38	214	368
009-1603-0010	009-1603-0020	10	11-1/2	250	48	342	540
009-1923-0010	009-1923-0020	12	13-3/4	250	48	503	732
009-2243-0010	009-2243-0020	14	15-3/4	250	68	573	845
009-2563-0010	009-2563-0020	16	17-3/4	250	78	765	1130
009-2883-0010	009-2883-0020	18	20	250	106	946	1408

* Assembled weight



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com