

Eagle Composite UNI-VAPOR



Vapor Recovery Service Hose

- Application:** Petrochemical and petroleum Vapor recovery systems
- Carcass:** Multiple layers of polypropylene fabric, film and polyester barrier layers
- Cover:** Abrasion Resistant PVC impregnated fabric
- Reinforcement:** High tensile strength galvanized internal and external wire.
- Temperature:** -22°F to +176°F (-30°C to +80°C)
- Branding:** EAGLE COMPOSITE UNI-VAPOR 150 PSI
- Safety Factor:** 4:1
- Couplings:** Carbon or Stainless (304 or 316), MNPT or Flange, Camlock

Features:

- Complete product compatibility for safe handling of all types of oil based 100% aromatic and Vapor.
- Tough PVC outer cover resists to dragging, wear, abrasion, UV and ozone resistance having maximum durability and safety.
- Electrical continuity is achieved by the two wire bonded of the end fittings, this helps dissipate accumulated charge and to avoid static flash.
- Suitable for 0.9 Bar Vacuum

| Part # | ID | Bend Radius | Max WP | Burst Pressure | Max Length | Weight |
|----------------|-----|-------------|--------|----------------|------------|--------|
| | in | in | PSI | PSI | ft | lbs/ft |
| 009-0163-1000I | 1 | 4.9 | 150 | 600 | 60 | 0.77 |
| 009-0243-1000I | 1.5 | 5.9 | 150 | 600 | 60 | 0.94 |
| 009-0323-1000I | 2 | 7.9 | 150 | 600 | 60 | 1.14 |
| 009-0483-1000I | 3 | 11.0 | 150 | 600 | 60 | 1.80 |
| 009-0643-1000I | 4 | 15.75 | 150 | 600 | 60 | 2.70 |
| 009-0963-1000I | 6 | 22.50 | 150 | 600 | 60 | 6.10 |
| 009-1283-1000I | 8 | 31.50 | 150 | 600 | 60 | 9.40 |



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777