

# Eagle Drafting/Hard Suction Hose

## Low Temp Water Suction Hose

**Application:** Suction side drafting, Dry Hydrant Connections, Trash pumps  
Construction and Mining, Solid Material Transfer  
Drafting from lakes, ponds, rivers, pools, wells, etc. during  
structural firefighting operations.

**Tube:** Cold Weather PVC

**Reinforcement:** Rigid PVC helix

**Temperature:** -22° to 140°F

**Couplings:** NH LH Female x NH RL Male  
or  
Storz Couplings



## Hose Features:

- Corrugated exterior for superior flexibility
- Smooth bore for unrestricted flow
- Lightweight and flexible in cold weather
- Clear sidewall permits visual check of material flow
- Weatherproof - highly resistant to ozone, salt water, and ultraviolet light
- External helix provides for easy drag

## Couplings Features:

- Manufactured from aircraft grade 6061-T6 seamless extrusions, Black hardcoat anodized
- Long Handle Swivels are forged T6, attached with hard alloy aluminum piston
- Three rocker lugs on 1" thru 3-1/2" and four rocker lugs on 4" thru 6"
- Storz Fittings offered in 5" only



NH Couplings



STORZ Couplings



Note: Over flexing or repeated flexing of hose within 18" of fitting is a common cause of hose failure.



**WARNING:** Cancer and  
Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Click for directions:

JGB® Headquarters  
Liverpool, NY 13088  
(315) 451-2770

Buffalo Branch  
Cheektowaga, NY 14225  
(716) 684-8224

Southeast Hub  
Charlotte, NC 28273  
(704) 588-9920

St. Louis Branch  
St. Louis, MO 63123  
(704) 588-9920

Williston Branch  
Williston, ND 58801  
(701) 774-2195

Houston Branch  
Pasadena, TX 77503  
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)