

Eagle EPDM Steam Hose

270 PSI Steam Hose



Application: The transfer of saturated and superheated steam up to 270 PSI and max 450°F in shipyards, chemical plants and industrial applications.

* Not recommended for washdown applications where detergent or oils are present.

* Proper draining of steam hose after each use will increase service life.

Tube: Black heat-resistant extruded EPDM. Not for steam cleaner use.

Reinforcement: High tensile steel wire braids.

Cover: Red heat-resistant EPDM rubber. Wrapped cover fabric impression. Pin-pricked cover to allow venting.

Temperature: -40°F to +410°F (Intermittent 450°F)

Branding: EAGLE EPDM STEAM 270 PSI WP

Standard Length: 50 or 100 feet

Couplings: Contact JGB for proper fitting recommendation and coupling procedure.

Warning:

Handling steam is very hazardous. If it is not properly controlled it can cause property damage, injury or even death. Selection for the proper application, usage, and maintenance will not only increase hose life but will insure safe operation for the user.

Part #	ID	OD	Min Bend Radius	WP	Weight
	in	in	in@68°F	psi	lbs/ft
*	1/2	0.98	5	270	.29
*	3/4	1.26	7-1/2	270	.53
010-0161-0270I	1	1.50	10	270	.61
*	1-1/4	1.81	12-1/2	270	.86
*	1-1/2	2.05	15	270	.93
010-0321-0270I	2	2.64	20	270	1.38

* Non stock



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com