

Eagle Flexcrete Mortar TPU

Concrete Boom Hose

Application: Lay-flat boom tip hose ideal for ICF forms, columns and tall walls where space is at a minimum.

Tube: Extruded thermoplastic polyether based polyurethane (TPU)

Reinforcement: Circular woven Aramid Fiber, "extra-strong yarn"

Cover: Extruded TPU Yellow cover, bonded to lining

Branding: 4" EAGLE FLEXCRETE MORTAR TPU 1250 PSI WP

Standard Coupling: 1-Piece High Pressure Rapid Crimp, Heavy Duty



Features:

- Meets/Exceeds ASME Requirements
- 1/3 the weight
- Operator Friendly
- More consistent flow at lower placement rates
- Ease of pour in tight areas
- Bright color for visibility and safety
- Superior resistance to weather and aging
- Cleans up easily

Part #	ID	Wall	WP	Burst	Tensile Strength		Weight
	in	in	psi	psi	x1000 lbs	tons	lbs/ft
008-0643-1250I	4	0.17	1250	2500	172	80	1.34
008-0803-1250I	5	0.17	1250	2500	179	81.5	1.48



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com