

# Eagle Gravity Fuel Drop



## Eagle Gravity Fuel Drop Hose

**Application:** Designed to deliver gasoline, diesel fuel, kerosene and fuels with aromatic content to 40%.

**Tube:** NBR/PVC tube, smooth bore with embedded Safety Ohm ground wire in the hose wall

**Reinforcement:** Rigid clockwise PVC helix, one braid of high tensile polyester yarn reinforcement

**Temperature:** -10°F to +140°F

**Lengths:** 100 ft lengths

## Features:

- \*\* Up to 50% lighter than conventional rubber hose.
- Higher transfer pressures.
- Easy to drag with "Go-Glide" external clockwise PVC helix.
- Safety Ohm ground wire embedded into hose wall to help prevent the build-up of static electricity. Wire must be secured to ground to dissipate static electricity.

Part #	ID	OD	Reinf. Spirals	MAX WP @ 68°F	Vacuum @ 68°F	Weight	Min Bend Radius
	in	in		psi	mm/Hg	lb/ft	in
009-0324-0120I	2	2.68	1	70	29.9	1.13	5
009-0484-0120I	3	3.68	1	65	29.9	1.37	6
009-0644-0121I	4	4.8	1	65	29.9	2.16	8



Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
Liverpool, NY 13088  
(315) 451-2770

**Buffalo Branch**  
Cheektowaga, NY 14225  
(716) 684-8224

**Southeast Hub**  
Charlotte, NC 28273  
(704) 588-9920

**St. Louis Branch**  
St. Louis, MO 63123  
(704) 588-9920

**Williston Branch**  
Williston, ND 58801  
(701) 774-2195

**Houston Branch**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)