

Eagle OILVAC

150 PSI Corrugated



Application: Designed for handling crude oil, frack solutions and slurries in oilfield vacuum tank service

Note: For applications up to 35% aromatics. Not for use with refined petroleum products or high concentrations of chemicals.

Tube: NBR/SBR – black, smooth, oil resistant

Reinforcement: High tensile textile cord; dual steel helix

Cover: NBR/SBR – black, flat corrugated with cloth impression, oil, abrasion, weather & ozone resistant

Temperature: -40°F to +185°F

Branding: EAGLE OILVAC 150 PSI WP

Couplings: Contact JGB for proper fitting recommendation and coupling procedure

Part #	ID	OD	Min Bend Radius	WP	Weight
	in	in	in	psi	lbs/ft
009-0322-0155I	2	2.48	5	150	1.09
009-0482-0155I	3	3.46	7.5	150	1.71
009-0642-0155I	4	4.53	12	150	2.29
009-0962-0155I	6	6.65	21	150	4.91
009-1282-0152I	8	8.86	31.5	150	8.62

* Full Vacuum



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com