

JGB® Enterprises



Lay Flat
Water Transfer

Eagle Water Transfer PU



Heavy Duty Polyurethane (PU) Layflat 200 PSI for 8" & 10" Hose

Large Diameter Hose (LDH)

Application: Construction sites, waste water industry, agriculture and mining, transport of abrasive materials, flexible pipeline even in extreme terrain, irrigation and sludge disposal, for heavy duty service under toughest conditions. Perfectly prepared for hydraulic fraction in shales and oil fields.

Tube: PU

Cover: PU, Ribbed cover or smooth cover

Reinforcement: Polyester-Nylon textile

Temperature: -58°F to 176°F

Branding: EAGLE PU WATER TRANSFER

Color: Black standard, blue, green, or red upon request

Package: Rolled, packed on steel reel

Standard Length: 100 ft (30m), 200 ft (61m), 300 ft (91.5m), 330 ft (100m) 660 ft (200m)

Mfg. Technology: Through-the-weave-technology

ID	Nom. OD	Max WP	Burst	Wall Thickness	Tensile Strength	Weight
in	in	psi/bar	psi/bar	in	lbs	lbs/ft
4	4 3/16	200/13	600/39	0.150	22000	
5	5 3/16	200/13	600/39	0.150	26400	
6	6 5/16	200/13	600/39	0.150	33000	1.07
8	8 5/16	200/13	600/39	0.170	89000	2.01
10	10 3/8	200/13	600/39	0.170	100100	2.55
12	12 7/16	200/13	450/30	0.180	134000	3.62
16	16 7/16	100/8	300/20	0.190		



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777