

Eagle OILFLEX

150 PSI Tank Truck Hose



Application: Suction and discharge application in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

Tube: Black conductive, oil resistant Nitrile (NBR)

Reinforcement: High tensile textile cord, double steel helix

Cover: Red corrugated - abrasion, hydrocarbon and ozone resistant

Temperature: -40°F to +180°F

Branding: EAGLE OILFLEX 150 PSI WP

Couplings: Contact JGB for proper fitting recommendation and coupling procedure

Part #	ID	OD	Bend Radius	WP	Weight
	in	in	in	psi	lbs/ft
009-0243-0150I	1-1/2	1.97	3	150	0.74
009-0323-0150I	2	2.52	3	150	1.06
009-0483-0150I	3	3.54	4	150	1.85
009-0643-0150I	4	4.65	6	150	2.60
009-0963-0150I	6	6.77	18	150	6.00
009-1283-0150I	8	8.86	25	150	9.00

* Full Vacuum



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com