

Eagle Orange/Clear



Eagle Orange/Clear Suction & Discharge Hose

Application: Fish suction and rental/construction pumping.

Construction: Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Temperature: -13°F to + 140°F

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Rated for both suction & discharge
- Clear sidewall permits visual check of material flow

Part #	ID	OD	Weight	Std. Length	Working Pressure	Vacuum Rating	Min Bend Radius
	in	in	lbs/ft	ft	psi	in/HG	in
007-0240-0100*	1-1/2	2.03	0.47	100	110	29	2.5
007-0320-0100I	2	2.60	0.69	100	100	29	4
007-0400-0100*	2-1/2	3.01	0.74	100	100	29	5
007-0480-0100I	3	3.70	1.13	100	100	28	6
007-0640-0080I	4	4.78	1.74	100	80	28	7
007-0960-0072I	6	7.17	3.88	20,60,100	70	28	10
007-1280-0060I	8	9.34	5.55	20,25	60	28	16
007-1600-0040I	10	11.63	8.90	20,25	40	28	25
015-0192-0020I	12	13.66	10.30	20	30	25	45

* Not standard-call for availability.



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com