

Eagle Slim Hole Rotary

Oilfield Drilling Hose



Application: Rotary hose, specially designed for use in portable, work-over and seismograph drilling rigs.

Tube: Oil resistant synthetic rubber.

Reinforcement: Four or six spiral wires for sizes -16 through -40 and four high tensile steel braids for size -48.

Cover: Abrasion, ozone, hydrocarbon and flame resistant synthetic rubber.

Temperature: -40° F (-40° C) to 200° F (+93° C) constant operation.
-40° F (-40° C) to 176° F (+80° C) ambient temperature

Safety Factor: 4:1 for ID sizes 1" to 2".
3:1 for ID sizes 2 1/2" to 3".

Couplings: Male NPT API Style.

Lengths: -24 through -48: 100' lengths.

Size Code	Construction	Nom. ID		Nom OD		Max Working Pressure †	Min Bend Radius		Approx. Weight
		in	mm	in	mm		in	mm	
16	4 Spiral	1	25	1.52	38.7	5,000	12.2	305	134
20	6 Spiral	1 1/4	32	1.96	49.8	5,000	16.8	419	241
24	6 Spiral	1 1/2	38	2.26	57.3	5,000	20.3	508	322
32	6 Spiral	2	51	2.79	70.9	5,000	25.4	635	447
40	4 Spiral	2 1/2	54	3.20	81	3,000	28.8	720	426
48	4 Braids	3	76	4.13	100	2,000	36.4	910	521

† Minimum burst pressure 4:1 safety factor for ID sizes 1" to 2" and 3:1 for ID sizes 2 1/2" to 3".



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com