

# Eagle Water Discharge 150 PSI

## Medium Duty Water Discharge



**Application:** Water discharge applications in construction, industry, and agriculture.

**Tube:** Synthetic rubber

**Reinforcement:** High-tensile synthetic textile

**Cover:** Weather and ozone resistant synthetic rubber

**Temperature:** -13°F to +158°F

**Branding:** EAGLE WATER DISCHARGE 150 PSI WP

**Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	WP	Min Burst	Weight	Length
	in	in	psi	psi	lbs/ft	ft
005-0242-0150I	1.50	1.85	150	450	0.60	100
005-0322-0150I	2.00	2.36	150	450	0.80	100
005-0402-0150I	2.50	2.91	150	450	1.12	100
005-0482-0150I	3.00	3.46	150	450	1.47	100
005-0642-0150I	4.00	4.53	150	450	2.21	100
005-0962-0150I	6.00	6.50	150	450	3.07	100
005-1282-0150I	8.00	8.74	150	450	5.45	100
005-1602-0150I	10.00	10.63	150	450	7.17	100



Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
Liverpool, NY 13088  
(315) 451-2770

**Buffalo Branch**  
Cheektowaga, NY 14225  
(716) 684-8224

**Southeast Hub**  
Charlotte, NC 28273  
(704) 588-9920

**St. Louis Branch**  
St. Louis, MO 63123  
(704) 588-9920

**Williston Branch**  
Williston, ND 58801  
(701) 774-2195

**Houston Branch**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)