

JGB Enterprises



Water Discharge

JGB Eagle Water Discharge HD

Eagle Water Discharge HD Hose



Application: Use for agricultural, quarry, irrigation, mining, construction and industrial applications

Tube: Premium Red PVC

Reinforcement: Two spiral plies and longitudinal silk cords

Cover: Premium Red PVC

Temperature: -10°F To 150°F

Branding: EAGLE WATER DISCHARGE HD

Packaging: Cut and coupled to length

Couplings: Standard short shank aluminum, malleable or brass couplings, Steel Bauer

Part #	ID	Apprx. Wall Thickness	WP	Weight
	in	in	psi	lbs
008-0241-0150I	1.5	.075	150	.20
008-0321-0150I	2	.080	150	.28
008-0481-0150I	3	.095	150	.54
008-0641-0125I	4	.100	125	.67
008-0961-0115I	6	.105	115	1.25
008-1281-0070I	8	.110	70	1.48
008-1926-0040I	12	.112	40	2.43

Standard Size	MxF	CxE
1 1/2"x50'	A008-0241-1650	A008-0241-3550
2"x50'	A008-0321-1650	A008-0321-3550
3"x50'	A008-0481-1650	A008-0481-3550
4"x50'	A008-0641-1650	A008-0641-3550
6"x50'	A008-0961-1650	A008-0961-3550



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777