

Eaglewash Carpet Cleaning

Eaglewash Carpet Cleaning Hose



Application: Specially designed for use on pressure washer machines with working pressures up to 3625 psi and temperatures up to 250°F (300°F intermittent).

Tube: Synthetic rubber, resistant against cold and hot water with usual cleaning agents.

Reinforcement: One braid of high tensile steel wire.

Cover: Abrasion and ozone resistant synthetic rubber, smooth only.

Temperature: -40°F to 250°F (300°F Intermittent)

Packaging: 400 ft, 2 piece reels or cut-to-length coils

Branding: 1/4" EAGLEWASH I PRESSURE WASHER HOSE 3625 PSI MAX WP INTERMITTENT 300 DEG F #Q##

Couplings: Hydraulic 100R1 type crimped to fitting manufacturer specifications

Colors: Blue, Gray, Black

Features:

- Available in bulk, 50 ft., 100 ft., and custom lengths
- Lightweight and easy to handle
- A unique cover compound gives JGB Eaglewash Carpet Cleaning hoses the durability and flexibility to handle abrasion and normal cleaning chemicals used in the wash industry.

Part #			Nom. ID	Nom. OD	Bend Radius	Burst	Max. Oper. Pressure	Weight
Black	Blue	Grey	in	in	in	psi	psi	lb/ft
168-0042-3000I	169-0046-3001I	169-0047-3001I	1/4	0.519	1.38	12,009	3625	.12



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com