

# Eaglewash I

## Eaglewash I Pressure Washer Hose



**Application:** For use on pressure washer machines with working pressures up to 4000 psi and temperatures up to 310°F.

**Tube:** Synthetic rubber, resistant against cold and hot water with usual cleaning agents.

**Reinforcement:** One braid of high tensile steel wire.

**Cover:** Abrasion and ozone resistant synthetic rubber, wrapped or smooth.

**Temperature:** 14°F to 310°F

**Packaging:** 500 ft 2 piece reels or cut-to-length coils

**Branding:** 3/8" EAGLEWASH 4001 PRESSURE WASHER HOSE PSI / 310 DEG F #Q##

**Couplings:** Hydraulic 100R1 type crimped to fitting manufacturer specifications

**Colors:** Blue, Gray, Black

## Features:

- Available in bulk, 50 ft., 100 ft., and custom lengths
- Lightweight and easy to handle
- A unique cover compound gives JGB Eaglewash I hoses the durability and flexibility to handle abrasion and normal cleaning chemicals used in the wash industry.

Part #			Nom. ID	OD	Bend Radius	Min Burst	Max. Oper. Pressure	Weight
Black	Blue	Grey	in	in	in	psi	psi	lbs/ft
168-6006-30011	168-0066-40001	168-0067-40001	3/8	.59	2.6	12,183	4061	.148



Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
Liverpool, NY 13088  
(315) 451-2770

**Buffalo Branch**  
Cheektowaga, NY 14225  
(716) 684-8224

**Southeast Hub**  
Charlotte, NC 28273  
(704) 588-9920

**St. Louis Branch**  
St. Louis, MO 63123  
(704) 588-9920

**Williston Branch**  
Williston, ND 58801  
(701) 774-2195

**Houston Branch**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)