

# \*EnviroDuct®

*This product is not recommended for aircraft ground support applications.*

## 1399-SD/1899-HD *Insulated and Non-Insulated EnviroDuct®*

**Application:** Air conditioning, ambient air movement, dehumidification  
**Construction:** PVC/Polyester Substrate with Steel Wire Helix, Sewn Construction  
**Weight:** 1399-SD: 13 oz./yd.<sup>2</sup> (441 g/m<sup>2</sup>), 1899-HD: 18 oz./yd.<sup>2</sup> (610 g/m<sup>2</sup>)  
**Temperature:** -20° to 180° F (-29° to 82° C)



**1399-SD/1899-HD**

### Pitch

### Diameters

<b>Standard Pitch:</b>	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
<b>Expanded Pitch:</b>	7" (18 cm)	12" (300 mm) or Larger

**Wire:** Hard-Drawn Steel  
**Inside Diameter:** 6" - 36" (150 - 900 mm)  
**Length:** 15', 25' (4.5, 7.5 m)  
**Color:** Black, Blue, Desert Tan, Green, Olive Drab, Red, White, Yellow  
**Optional Wearstrip:** Heavy-Duty Extruded PVC  
**Optional End Finishes:** Belt Cuff, Soft Cuff, Wire Rope Coupling

## High Polish

**Application:** Air conditioning, ambient air movement, dehumidification, drying, general purpose blower hose  
**Construction:** PVC/Polyester Substrate with Steel Wire Helix, Sewn Construction  
**Weight:** 14 oz./yd.<sup>2</sup> (475 g/m<sup>2</sup>)  
**Temperature:** -20° to 180° F (-29° to 82° C)



**High Polish**

### Pitch

### Diameters

<b>Standard Pitch:</b>	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) & Larger Diameters
<b>Expanded Pitch:</b>	7" (18 cm)	12" (300 mm) and Larger Diameters

**Wire:** Hard-Drawn Steel  
**Inside Diameter:** 6" - 36" (150 - 900 mm)  
**Length:** 15', 25' (4.5, 7.5 m)  
**Color:** White  
**Optional Wearstrip:** Heavy-Duty Extruded PVC  
**Optional End Finishes:** Belt Cuff, Soft Cuff, Wire Rope Coupling, Screw Clamp Cuff, Zipper Cuff

## 15WK *Insulated and Non-Insulated EnviroDuct®*

**Application:** Portable heater ducting with moderately high heat content  
**Construction:** Thermoplastic Elastomer with Warp Knit Backer, Steel Wire Helix, Sewn Construction  
**Weight:** 15 oz./yd.<sup>2</sup> (509 g/m<sup>2</sup>)  
**Temperature:** -65° to 350° F (-54° to 177° C) intermittent



**15WK**

### Pitch

### Diameters

<b>Standard Pitch:</b>	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
<b>Expanded Pitch:</b>	7" (18 cm)	12" (300 mm) or Larger

**Wire:** Hard-Drawn Steel  
**Inside Diameter:** 6" - 36" (150 - 900 mm) Larger diameters available upon request.  
**Length:** 15', 25' (4.5, 7.5 m)  
**Color:** Black, Desert Tan, Olive Drab, White, Yellow  
**Optional Wearstrip:** Heavy-Duty Extruded PVC  
**Optional End Finishes:** Pinlock Coupling, Belt Cuff, Wire Rope Coupling, Soft Cuff

*\* EnviroDuct® is a registered trademark of ABC Industries, Inc.*

Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
 Liverpool, NY 13088  
 (315) 451-2770

**Buffalo Branch**  
 Cheektowaga, NY 14225  
 (716) 684-8224

**Southeast Hub**  
 Charlotte, NC 28273  
 (704) 588-9920

**St. Louis Branch**  
 St. Louis, MO 63123  
 (704) 588-9920

**Williston Branch**  
 Williston, ND 58801  
 (701) 774-2195

**Houston Branch**  
 Pasadena, TX 77503  
 (281) 930-7777