

J-FLEX® 4SH XFLEX

J-FLEX XFlex Hydraulic Hose



- Application:** Hydraulic systems with high peak pressures and arduous operating conditions needing extremely high flexibility. Due to its extreme flexibility, XFlex is perfect for use in extraordinarily tight positions.
- Tube:** Oil-resistant synthetic rubber
- Reinforcement:** 4 braids of high tensile steel spirals
- Cover:** Black MSHA, made of synthetic rubber, resistant to oil and weather conditions
- Temperature:** -40°F to +248°F (257°F intermittent)
- Branding:** J-FLEX® DIN EN 856 4SH XFlex 6150 PSI/424 BAR MAX WP MSHA
- Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	Bend Radius	WP	Burst Pressure	Weight
	in	in	in	psi	psi	lbs/ft
182-4020-5100IM	1-1/4	1.78	14.0	5,075	20,300	1.68
182-4024-4200IM	1-1/2	2.08	20.0	4,205	16,820	2.08
182-4032-3625IM	2	2.66	25.0	3,625	14,790	2.92



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777