

## J-FLEX® 13M SAE 100R13

Hydraulic

### High Peak Pressure Hydraulic Hose with Improved Flexibility

**Application:** Designed for hydraulic systems with high peak pressures and arduous operating conditions (pulsing, flexing)

**Tube:** Nitrile; Mineral, vegetable, **BIO OIL**, and glycol based hydraulic oil resistant

**Reinforcement:** 4 or 6 high tensile steel spirals

**MSHA Fire Resistant Cover:** Abrasion, ozone, & hydrocarbon resistant special synthetic rubber

**Temperature:** -40°F to 250°F



Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
182-9012-5000IM	3/4	1.22	5500	22000	5.9	0.83
182-9016-5000IM	1	1.51	5500	22000	7.1	1.13
182-9024-5000IM	1-1/2	2.22	5000	20000	19.7	3.00
182-9032-5000IM	2	2.76	5000	20000	21.7	4.20

\* For 1-1/4" refer to 15M SAE 100R15 182-5020-6000IM



Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
Liverpool, NY 13088  
(315) 451-2770

**Buffalo Branch**  
Cheektowaga, NY 14225  
(716) 684-8224

**Southeast Hub**  
Charlotte, NC 28273  
(704) 588-9920

**St. Louis Branch**  
St. Louis, MO 63123  
(704) 588-9920

**Williston Branch**  
Williston, ND 58801  
(701) 774-2195

**Houston Branch**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)