

J-FLEX® 15M SAE 100R15

High Peak Pressure Hydraulic Hose with Improved Flexibility

Application: Designed for hydraulic systems with high peak pressures and arduous operating conditions (pulsing, flexing)

Tube: Nitrile; Mineral, vegetable, **BIO OIL**, and glycol based hydraulic oil resistant

Reinforcement: 4 or 6 high tensile steel spirals

MSHA Fire Resistant Cover: Abrasion, ozone, & hydrocarbon resistant special synthetic rubber

Temperature: -40°F to 250°F



Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
182-5012-6000IM	3/4	1.23	6000	24000	8.3	0.99
182-5016-6000IM	1	1.50	6000	24000	9.8	1.36
182-5020-6000IM	1-1/4	1.94	6000	24000	17.5	2.32
182-5024-6000IM	1-1/2	2.22	6000	24000	22.0	3.00



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com