


J-FLEX® 1 SAE 100R1AT/1SN

Hydraulic

Low-Medium Pressure Hydraulic Hose



- Application:** Designed for low-medium pressure hydraulic systems in industry and agriculture.
- Tube:** Synthetic rubber, resistant against hydraulic fluids
- Reinforcement:** One braid of high tensile steel wire
- Cover:** Abrasion and ozone resistant synthetic rubber. **Note:** various covers available
- Temperature:** -40°F to 212°F (max 248°F intermittent)
- Branding:** J-FLEX® 1 SAE 100R1AT / 1SN EN 853 1525 PSI
- Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
171-1004-3265I	1/4	0.52	3265	13060	3.93	0..13
171-1006-2610I	3/8	0.67	2610	10440	5.11	0.19
171-1008-2320I	1/2	0.8	2320	9280	7.08	0.24
171-1012-1525I	3/4	1.08	1525	6100	9.44	0.38
171-1016-1275I	1	1.39	1275	5100	11.81	0.56



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777