

J-FLEX® 2M 2SN/SAE 100R2AT

Medium - High Pressure Hydraulic Hose



Application: Designed for medium-high pressure hydraulic systems in industry and agriculture.

Tube: Synthetic rubber, resistant against hydraulic fluids

Reinforcement: Two braids of high tensile steel wire

MSHA Approved Cover: Abrasion and ozone resistant synthetic rubber. Note: various covers available. Blue cover available

Temperature: -40°F to 212°F (max 248°F intermittent)

Branding: J-FLEX® 2M SAE 100RAT / 2SN EN 853 2395 PSI

Couplings: Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
172-1004-5800IM	1/4	0.57	5800	23200	3.93	0.21
172-1006-4800IM	3/8	0.72	4800	19200	5.11	0.30
172-1008-4000IM	1/2	0.84	4000	16000	7.08	0.36
172-1010-3625IM	5/8	0.97	3625	15000	7.87	0.44
172-1012-3120IM	3/4	1.13	3120	12480	9.44	0.56
172-1016-2400IM	1	1.46	2400	9600	11.81	0.83
172-1020-1815IM	1 1/4	1.86	1815	7260	16.53	1.19
172-1024-1305IM	1 1/2	2.11	1305	5220	19.68	1.46
172-1032-1160IM	2	2.63	1160	4640	24.80	1.88



Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com