

JGB Enterprises



Service Plug

Accessories



HOW TO USE

The Service Plug is developed to plug hoses or rigid pipes to avoid oils and chemicals from contaminating the environment and to preserve costly oils and liquids inside systems during maintenance and repair. It can also be used to protect machine channels from dust and corrosion and when cleaning or painting, to prevent water, paint, dust and pollution from harming system and components

IMPORTANT

For use in non pressurized systems and vacuum systems!

MATERIAL

The Service Plug is produced in high quality oil resistant rubber

DIMENSIONS

For channels and holes between (micro) 0.04 - 0.4" / (standard) 0.16 - 0.91" / (XL) 0.47 - 1.7"

TEMPERATURE

-25°C - +90°C / -15°F - +195°F

TOOLS

No tools needed! Use your hand. Insert, push then push and twist in the same action

CUTTING

If the plug reaches the bottom it might be cut. If you chose to cut a plug in place, make sure to leave enough material outside the hole that you easily can remove the plug



JGB Headquarters
115 Metropolitan Dr.
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
2540 Walden Ave.
Cheektowaga, NY 14225
(716) 684-8224

Southeast Regional Hub
1407 Westinghouse Blvd.
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
9707 Green Park Industrial Dr.
St. Louis, MO 63123
(314) 487-3144

Williston Branch
520 Bean Dr.
Williston, ND 58801
(701) 570-2945

Houston Branch
619 E. Sam Houston Pkwy.
Suite 200
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com