

J-FLEX® 10K Jack Hose

Hydraulic Jack Hose

- Application:** Designed for hydraulic hack applications
- Tube:** Oil resistant synthetic rubber
- Reinforcement:** Two braids of high tensile steel wire.
- Cover:** MSHA, abrasion and weather resistant synthetic rubber
- Temperature:** -40°F to +212°F depending on the medium
- Branding:** J-FLEX® 10K JACK HOSE 10,000PSI WP / 20,000PSI BP MSHA
- Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.



Part #	ID	OD	Bend Radius	Max WP	Test Pressure	Burst Pressure	Weight
	in	in	in	psi	psi	psi	lbs/ft
172-8004-1000I	1/4	0.59	4	10,000	12,000	20,000	0.20
172-8006-1000I	3/8	0.75	5	10,000	12,000	20,000	0.34

3/8" J-FLEX 10K JACK HOSE 10,000 PSI WP / 20,000 PSI BP MSHA IC-8/17

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777