

# Valves

## Oil & Gas Industry Valves

JGB Enterprises, a full line supplier of high-performing industrial valves to its clients in the oil & gas industry including Butterfly Valves, Gate Valves, Check Valves, and more. Our relationships with national manufacturers and suppliers allow us to deliver the valves you need fast!

### WAFER BUTTERFLY VALVE (Drop in Style)

ANSI 125/150 Flange Capable

**Sizes:** 2" - 12"  
**Pressure:** 200 PSI NSCP  
**Features:** Short Neck, Notched Body, Pinless Disc, Lever or Gear Operated  
**Body Material:** Ductile Iron, Epoxy Coated  
**Disc Materials:** Ductile Iron Nickel Plated, Aluminum Bronze, Stainless Steel, Nylon Coated  
**Seat Materials:** Buna, Viton  
**Stem:** Available in Double D or Square Stem, 416 Stainless Steel



### WAFER BUTTERFLY VALVE

ANSI 125/150 Flange Capable

**Sizes:** 2" - 24"  
**Pressure:** 200 PSI NSCP  
**Features:** 4 Alignment Holes, Pinless Disc, Lever or Gear Operated  
**Body Material:** Ductile Iron, Epoxy Coated  
**Disc Materials:** Ductile Iron - Nickel Plated, Aluminum Bronze, Stainless Steel  
**Seat Materials:** Buna, EPDM, Natural Rubber  
**Stem:** Double D Style, 416 Stainless Steel



### LUG STYLE BUTTERFLY VALVE

**Sizes:** 4" - 16"  
**Pressure:** 200 PSI at ambient temperature (70°F)  
**Features:** For use between two 150 lb. flanges. Will lock "open" or "closed"  
**Body Material:** Ductile Iron, ASTM A536  
**Disc Materials:** Aluminum bronze disc, ASTM B148, ALY.954  
**Seat Materials:** Buna-N seal  
**Stem:** Stainless steel top and bottom stems



### CHECK VALVES

**Sizes:** 4" - 16"  
**Pressure:** 4" - 12": 200 PSI @ 150 °F, 14" - 16": 150 PSI @ 150 °F  
**Features:** Suitable for municipal and industrial applications  
**Body Material:** Ductile Iron body with ASME Class 125 flanges  
**Disc Materials:** Steel & fabric reinforced Buna-N  
**Cast Body Gasket:** A536 60-45-12 Ductile Iron Lexide NK-511 (non-asbestos)



### KNIFE GATE VALVES

- Conform to TAPPI TIS 405.8 face-to-face.
- Tested to MSS SP-81.
- Full Port.
- Full lug body drilled and tapped to ASME Class 150.
- Bi-Directional shut-off resilient seated design.

**Sizes:** 4" - 16"  
**Pressure:** 150 PSI CWP



### FLANGED GATE VALVE

**Sizes:** 2" - 16"  
**Pressure:** 250 psi Non Shock CWP  
**Body Material:** Cast Iron  
**Disc Materials:** Cast Iron Wedge  
**Seat Materials:** Buna-N seal  
**Stem:** Bronze

Meets MSS SP-70, ASTM A126, AWWA C509, FM, and UL standards



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Download the JGB® Mobile App



Click for directions:

**JGB® Headquarters**  
 Liverpool, NY 13088  
 (315) 451-2770

**Buffalo Branch**  
 Cheektowaga, NY 14225  
 (716) 684-8224

**Southeast Hub**  
 Charlotte, NC 28273  
 (704) 588-9920

**St. Louis Branch**  
 St. Louis, MO 63123  
 (704) 588-9920

**Williston Branch**  
 Williston, ND 58801  
 (701) 774-2195

**Houston Branch**  
 Pasadena, TX 77503  
 (281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)