

Thunderblast® Sandblast Hose



Thunderblast® Sandblast Hose 2/4 Ply

- Application:** Specially designed hose for use in all abrasive blast applications, suitable for all commonly used blasting media
- Tube:** Black Static Conductive Natural
- **4ply:** 1/2" - 3/4" ID have 1/4" tube thickness, 1" - 2" ID have 5/16" tube thickness.
 - **2ply:** All sizes, 1/4" tube thickness
- Reinforcement:** High Tensile Textile Plies
- Cover:** Black Abrasion Resistant SBR
- Temperature:** -40°F to +185°F (-40°C to +85°C)
- Branding:** THUNDERBLAST® 4 PLY 150 PSI WP
- Standards:**
- EN ISO 3861
 - **Abrasion loss Value:** According to DIN 53516 ≤ 60 mm³

Features:

- With black high abrasion, static conductive natural rubber tube
- Black abrasion resistant cover with green layline
- All sizes rated to 150 PSI
- Bulk hose available in 200 foot lengths

Part #	ID	OD	Plies	WP	Weight
	in	in		psi	lbs/ft
011-2082-0150 / 011-4082-0150	1/2	1-1/16 / 1-3/16	2/4	150 / 150	.36 / .38
011-2120-0150 / 011-2122-0150	3/4	1-5/16 / 1-1/2	2/4	175 / 150	.48 / .69
011-2162-0151 / 011-4162-0150	1	1-1/2 / 1-7/8	2/4	175 / 150	.78 / 1.03
011-2202-0175 / 011-4202-0150	1 1/4	1-7/8 / 2-5/32	2/4	175 / 150	.83 / 1.23
011-4242-0150	1 1/2	2-3/8	4	150	1.33
011-0322-0150I	2	2-7/8	4	150	1.66

Hose Size (in)	Plies	Quick Coupling Size (in)	External Nozzle Holders Size (in)
1/2x1-1/16	2	1/2 Aluminum	1/2 Aluminum
3/4x1-1/2	4	3/4 Aluminum	3/4 Aluminum
1x1-7/8	4	1 Aluminum	1 Aluminum
1-1/4x2-5/32	4	1-1/4 Aluminum	1-1/4 Aluminum
1-1/2x2-3/8	4	1-1/2 Aluminum	1-1/2 Aluminum

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63123
(704) 588-9920

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com