

WATER BLAST HOSE



Description: Very High Pressure Waterblast Hose
Tube: NBR (Nitrile rubber)
Cover: NBR (Nitrile rubber)
Reinforcement: 4 Spiral Layers
Temperature: -40°F to 160°F

Series	ID	OD	WP	Burst Pressure	Tensile Strength	Bend Radius	Weight
	in	in	psi	psi	lbs	in	lbs/ft
WB10	1/2"	0.969"	10000	25000	2976	8.00"	0.61
WB10	3/4"	1.27"	10000	25000	4452	8.25"	0.98
WB10	1"	1.528"	10000	25000	11034	14.00"	1.46

Series	ID	OD	WP	Burst Pressure	Tensile Strength	Bend Radius	Weight
	in	in	psi	psi	lbs	in	lbs/ft
WB15	3/8"	0.843"	18000	45000	2189	6.00"	0.57
WB15	1/2"	1.000"	16000	40000	3283	8.00"	0.85
WB15	3/4"	1.252"	14500	36250	6373	11.00"	1.20

Description: Ultra High Pressure Waterblast Hose
Tube: NBR (Nitrile rubber)
Cover: NBR (Nitrile rubber)
Reinforcement: 6 Spiral
Temperature: -40°F to 160°F

Series	ID	OD	WP	Burst Pressure	Tensile Strength	Bend Radius	Weight
	in	in	psi	psi	lbs	in	lbs/ft
WB20	1/2"	1.161"	20000	50000	4178	8.00"	1.17

Precautions

- Restricted to use as high pressure waterjetting hose where safety factors of 2.5:1 are the industry norm. Due to the safety critical nature of these very high pressure hoses, it is recommended that pre-fitted and tested assemblies are sourced.
- No warranty is given for assemblies made with non-approved fittings.
- JGB recommends referencing the recommended practices for the use of manually operated high pressure waterjetting equipment published by the Waterjet Technology Association (WJTA).



*** Disconnects and Hammer Unions also available

Download the JGB[®] Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

JGB Headquarters
 Liverpool, NY 13088
 (315) 451-2770

Buffalo Branch
 Cheektowaga, NY 14225
 (716) 684-8224

Southeast Hub
 Charlotte, NC 28273
 (704) 588-9920

St. Louis Branch
 St. Louis, MO 63123
 (704) 588-9920

Williston Branch
 Williston, ND 58801
 (701) 774-2195

Houston Branch
 Pasadena, TX 77503
 (281) 930-7777