

# Eagle EPDM Steam Hose

## High Pressure Steam Hose



**Application:** High pressure steam hose for saturated steam, used in closed steam systems in heating and cleaning applications, drain after use, also suitable for high pressure air and water applications

**Tube:** EPDM High temperature and steam resistant, black, smooth

**Reinforcement:** Steel wire braided

**Cover:** EPDM Red, high temperature, weather and ozone resistant, smooth with cloth impression, pin pricked

**Temperature:** -31°F to +410°F

**Branding:** EAGLE EPDM STEAM

**Standard Length:** 100 feet

**Packaging:** Coils with PE Wrapping

**Couplings:** Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	Bend Radius	WP	Burst	Weight
	in	in	in	psi	psi	lbs/ft
010-0081-0250I	1/2	0.98	2.56	261	2611	2.1
010-0121-0250I	3/4	1.26	3.74	261	2611	3.8
010-0161-0250I	1	1.50	4.92	261	2611	4.4
010-0201-0250I	1-1/4	1.81	6.30	261	2611	6.2
010-0241-0250I	1-1/2	2.05	7.48	261	2611	6.7
010-0321-0250I	2	2.64	10.03	261	2611	10.0



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters  
Liverpool, NY 13088  
(315) 451-2770

Buffalo Branch  
Cheektowaga, NY 14225  
(716) 684-8224

Southeast Hub  
Charlotte, NC 28273  
(704) 588-9920

St. Louis Branch  
St. Louis, MO 63111  
(314) 256-0833

Williston Branch  
Williston, ND 58801  
(701) 774-2195

Houston Branch  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)